



This application works for: TM1000A, PoE Digital Clock Controllers, Wifi Clock Controllers, and DotMatrix Products.

Installation Instructions:

1. Extract the downloaded .zip file to the desktop or other convenient location.
2. Double click "TMFlashSetup.exe" to install flash update software. (Win XP and newer)
3. When prompted to allow installer to install the application, select yes.
4. Choose either the default directory or choose custom installation directory.
5. Select "Agree" to Install, and follow the install wizard instructions.
6. Once complete, open web browser for the TimeMachines product being updated.
Note the IP Address and MAC address.
7. Open TMFlash (From shortcut on Desktop)


Operating Instructions:

1. Enter the IP address for the device to be updated. (For digital clocks, the button can be pressed twice rapidly to scroll the IP address.)
 2. The MAC address should be read automatically from the device being updated.
 3. Drag and drop the update file (".bin" extension) or click the drop area to open a file dialog.
- * When these are all accepted, the update button will be revealed.
 - * If for any reason the device and the update file do not match, an error will be shown. Verify that the file is for the device specified.
 - * Once the devices has been successfully updated, the application will allow update to additional devices.

Uninstall Instructions:

To uninstall, select Uninstall TMFlash from the start menu. This will completely remove the application and any files related to it from your computer.

Network	
Use DHCP	<input checked="" type="checkbox"/>
IP	10.10.42.27
Netmask	255.255.0.0
Gateway	10.10.0.1
Primary DNS Server	8.8.8.8
Secondary DNS Server	8.8.4.4
MAC	00:50:C2:D3:F0



Common Issues & Notes:

The most common problems with using TMFlash for updating TimeMachines products generally comes down to a couple of things:

- Firewall or Anti-Virus software blocking its function. Please try disabling these applications and retrying the update.
 - Trying to update across subnets. A broadcast message must be receivable from TimeMachines product to the Windows computer for the process to work. This may require re-locating the network connection points.
 - TFTP server running on update computer. The update processes uses TFTP, if there is already a TFTP server running, it must be disabled for the update process to work
 - Multiple network interfaces, such as active wired and WiFi, or VPN connections (virtual) connections can confuse the update software
- Note: WiFi clocks must be updated through the wired interface. Updating through WiFi is not supported.